

SuperPrint® Plus FL is a 13 oz. quality, economical choice for an all around outstanding front-lit banner or billboard material for UV, solvent or screen-printing. Both strong and durable, SuperPrint Plus FL prints vibrantly and consistently and is tear and fade resistant. Available in both matte and gloss finishes in widths ranging from 38" - 198".

### Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Support Cloth	DIN60001	Polyester	Polyester
Yard dtex	DIN60001	1100 x 1100 dtex	1000 x 1000 denier
Type of Coating	N/A	PVC	PVC
Total Weight	N/A	440 g/m <sup>2</sup>	13 oz.
Tensile Strength	DIN53354	120 x 110 kgF	290 x 245 lbs/in
Tear Strength (warp/weft)	DIN53363	22 x 19 kgF	46 x 40 lbs/in
Flame Resistance		NFPA701, B1	
Low Temperature (No Crack at:)	DIN53372	-30°C	-22°F
Fungus Resistance	N/A	N/A	N/A
Puncture Resistance	N/A	N/A	N/A
RF Weldable (Heat Sealable)		Yes	

### Applications

	Back-lit	Banner	Billboard	Block-out	Building Wrap	Display Systems	Truckside
Applications		■	■			■	

### Ink Printability

Solvent	Eco Solvent	UV	Screen Printing	Dye Transfer	Dye Direct
■	■	■	■		

### Available Sizes

Metric (m)	English (inches)
.965, 1.37, 1.60, 1.83, 2.03, 2.50, 2.60, 3.20, 5.00	38, 54, 63, 72, 80, 98, 102, 126, 198

Key: ■ - Excellent □ - Good

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guaranty and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)