

UltraCanvas™ Light C190 is 5.9 oz. and is woven 100% polyester that has been bath coated and then coated again on one side with our Universal coating. This coating technique allows you to print Solvent and UV on one side or dye sublimation on the other. Its light canvas structure makes it ideal for back-lit or front-lit graphics as well as most indoor and short-term outdoor applications including event tent structures. Available in widths ranging from 54" to 198".

Material Details

CHARACTERISTICS	TEST METHOD	METRIC	ENGLISH
Support Cloth	DIN 60001	100% Polyester	100% Polyester
Type of Coating	N/A	Single side coated	
Total Weight	DIN EN ISO 2286-2	190 g/m ²	5.9 oz/yd ²
Breaking Force [N/5cm]	DIN EN ISO 13934-1	Testing in progress	
Elongation at tear [%]	DIN EN ISO 13934-1	Testing in progress	
Tear Resistance [N/25mm]	DIN EN ISO 9073-4	Testing in progress	
Flame Resistance	DIN 4102	B1, ASTM E84	
Character	N/A	Light canvas texture	
Added Value	N/A	Can be back-lit and front-lit	
RF Weldable (Heat Sealable)		Testing in progress	

Applications

	Art Reprographic	Banners Indoor	Banners Outdoor	Displays	Flags	Theatrical	Tradeshow	Wall Covering
Applications	■	■	■	■		■	■	■

Ink Printability

Solvent	Eco Solvent	UV	Screen Printing	Dye Transfer	Dye Direct
■	■	■	■	■	■

Available Sizes

Metric (m)	English (inches)
2.05, 2.50, 3.10, 5.05	80, 98, 122, 198

Key: ■ - Excellent □ - Good

The information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. A legally binding guarantee of specific properties is not to be inferred from our specifications. They are given without guaranty and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)