

## Artist Light C185

### Product Description

Artist Light is a frontlit woven 185gsm, 100% polyester textile that has been coated on one side. The light woven structure is especially suited for exhibition walls and ceilings where show through or two-way graphics are required. Suitable for Eco-Solvent and UV printing and is B1 fire rated. Available up to 5.05 metre wide.

Artist Light is also available as an uncoated version (Artist Light U170) which is suitable for Latex and Dye Sublimation printing.

### Material Details

CHARACTERISTICS	TEST METHOD	METRIC
Support Cloth	DIN ISO 2286-2	100% Polyester
Type of Coating	N/A	Single side coated
Total Weight	DIN EN ISO 2286-2	185gsm
Binding	Warp Rip Weave (Woven)	
Breaking Force (N/5cm)	DIN EN ISO 13934-1	Warp: 1.521 N / Weft: 1.375 N (approx)
Tear Resistance (N/25mm)	DIN EN ISO 13937-2	Warp: 76 N / Weft: 77 N (approx)
Flame Resistance	DIN 4102-1	B1

### Applications

	Exhibition Walls & Roof Linings	Frontlit Outdoor Short Term	Window Blinds	Pasted Wallcovering (One piece)	SEG Frames	Backlit SEG Frames	Barrier Jackets	Fence Dressing	Flags
Application	■	■	■		■				

### Ink Printability: Artist Light - C185

Eco Solvent	UV	Latex	Dye Sublimation
■	■		

### Available Sizes

Measurements (Metric m)	
Width	Length
1.55	50
2.52	50
3.10	50
5.05	50

Disclaimer: A legally binding guarantee of specific material properties cannot be inferred from this datasheet the values presented are intended only as a guide of performance only. The information is given without guarantee and does not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for their specific purpose.