

Campaign Banner 440

Product Description

Campaign Banner is our entry level 440gsm frontlit banner PVC. It incorporates a 300 x 500 denier, 18 x 12 base cloth construction which ensures adequate tear and tensile strength, making it ideal for short term or one-off use applications. It is suitable for Eco-Solvent and UV inks, available up to 3.2-metre-wide, non-FR.

Material Details

CHARACTERISTICS	TEST METHOD	METRIC
Support Cloth	DIN 2076	Polyester (18 x 12)
Yarn (Thickness)	DIN EN ISO 2060	300 x 500 denier
Type of Coating	DIN 53352	PVC
Total Weight	DIN 53352	440gsm
Tensile Strength (Warp/weft)	DIN 53352	Warp: 635 N/5cm Weft: 450 N/5cm
Tear Strength (Warp/weft)	DIN 53356	Warp: 125 N Weft: 107 N
Low Temperature (No Crack at:)	DIN 53357	-20°C
RF Weldable	Not Recommended	
Flame Retardant	Non Fire Rated	

Applications

	Back-lit	Banner	Billboard	Block-out	Building Wrap	Display Systems	Truckside
Application		■					

Ink Printability

Eco Solvent	UV	Latex	Screen Printing	Dye Sublimation
■	■			

Key: ■ = Excellent □ = Good

Available Sizes

Measurements (Metric m)	
Width	Length
1.15	30
1.15	50
1.37	30
1.37	50
1.60	30
3.20	65

Disclaimer: A legally binding guarantee of specific material properties cannot be inferred from this datasheet the values presented are intended only as a guide of performance only. The information is given without guarantee and does not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for their specific purpose.