

Lightbox C205

Product Description

Lightbox is a frontlit/backlit 205gsm textile which displays an excellent white point and has an optimised coating to prevent show through, whilst giving excellent translucency in backlit applications. Its lightweight knitted construction is crease and bruise resistant and allows for a slight stretch when installing into SEG frame systems. It is suitable for Eco-Solvent, UV and 3rd Gen Latex printing and is B1 fire rated. Available in 3.1 and 5.05 metre wide rolls.

Material Details

CHARACTERISTICS	TEST METHOD	METRIC
Support Cloth	DIN ISO 2076	Polyester
Total Weight	DIN EN ISO 2286-2	205gsm
Binding	Knitted With Opaque Coating	
Salvage	Loose Selvedge	
Tensile Strength (Warp/Weft)	ISO 13934-1	Warp: 290 N/5 cm Weft: 1110 N/5 cm
Light Transmition	35%	
Flame Resistance	DIN EN 13501-1	B1

Applications

	Exhibition Walls & Roof Linings	Frontlit Outdoor Short Term	Window Blinds	Pasted Wallcovering (One piece)	SEG Frames	Backlit SEG Frames	Barrier Jackets	Fence Dressing	Flags
Application					■	■			

Ink Printability

Eco Solvent	UV	Latex	Dye Sublimation
■	■	■	

Available Sizes

Measurements (Metric m)	
Width	Length
3.10	50
5.05	50

Disclaimer: A legally binding guarantee of specific material properties cannot be inferred from this datasheet the values presented are intended only as a guide of performance only. The information is given without guarantee and does not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for their specific purpose.