

PET Greyback 225

Product Description

SuperSmooth Greyback 225 PET (polyester) is a blackout material 225 micron with excellent lay flat properties and a very good white point. It is ideal for pull-up, roller banner and single sided blackout display applications. Suitable for Eco-Solvent and UV Printing. Available up to 2.2 metres wide.



Material Details

CHARACTERISTICS	TEST METHOD	METRIC
Support Cloth	Polyethylene Terephthalate (PET)	
Type of Coating	N/A	PVC
Total Weight	DIN 53352/BS 3424	225 micron
Tensile Strength	DIN 53354/BS 3424	N/5cm Warp 982 / Weft 873
Tear Strength (Warp/weft)	DIN 53356/BS 3424	N/5cm Warp 34 / Weft 27
HA Weldable (Heat Sealable)	N/A	N/A
Flame Retardant	Non Fire Rated	

Applications

	Frontlit	Blockout	Pop-Up Display	Banner Stands	Scrolling Signs	Column Wraps
Application	■	■	■	■	■	

Ink Printability

Eco Solvent	UV	Latex	Dye Sublimation
■	■		

Available Sizes

Measurements (Metric m)	
Width	Length
0.914	50
2.20	50

Disclaimer: A legally binding guarantee of specific material properties cannot be inferred from this datasheet the values presented are intended only as a guide of performance only. The information is given without guarantee and does not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for their specific purpose.