

## Poplin PES C255

### Product Description

Poplin PES is our most popular frontlit textile. It has a knitted 255gsm construction for easy stretch on SEG frame systems and exhibition structures and is crease and wrinkle resistant. It is suitable for Eco-Solvent, UV and Screen printing and is B1 fire rated. Available up to 5.05 metres wide.

### Material Details

CHARACTERISTICS	TEST METHOD	METRIC
Support Cloth	DIN 60001	Polyester
Type of Coating	N/A	Digital coating on one side
Total Weight	DIN EN ISO 2286-2	255gsm
Binding	Knitwear	
Salvage	Loose Selvedge	
Flame Resistance	DIN 4102	B1

### Applications

	Exhibition Walls & Roof Linings	Frontlit Outdoor Short Term	Window Blinds	Pasted Wallcovering (One piece)	SEG Frames	Backlit SEG Frames	Barrier Jackets	Fence Dressing	Flags
Application		■			■				

### Ink Printability

Eco Solvent	UV	Latex	Dye Sublimation
■	■	■	

### Available Sizes

Measurements (Metric m)	
Width	Length
3.10	50
5.05	50

Disclaimer: A legally binding guarantee of specific material properties cannot be inferred from this datasheet the values presented are intended only as a guide of performance only. The information is given without guarantee and does not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for their specific purpose.