

## Superprint 2 440

### Product Description

Superprint 2 is a frontlit 440gsm economy matt laminated PVC banner. It incorporates a 1,000 x 1,000 denier, 12 x 12 base cloth construction ensuring excellent tear and tensile strength. With a high-quality surface that delivers consistent printing performance enabling this material to outperform all other economy 440gsm laminates currently available. It is suitable for Eco-Solvent, UV and Latex printing. Available up to 3.2 metres wide.

### Material Details

CHARACTERISTICS	TEST METHOD	METRIC
<b>Support Cloth</b> (Weave)	DIN 2076	Polyester (12 x 12)
<b>Yarn</b> (Thickness)	DIN EN ISO 2060	1,000 x 1,000
<b>Type of Coating</b>	DIN 53352	PVC
<b>Total Weight</b>	DIN 53352	440gsm
<b>Tensile Strength</b>	DIN 53352	N/5 cm Warp 1,850 / Weft 1,350
<b>Tear Strength</b> (Warp/weft)	DIN 53356	N - Warp 350 / Weft 300
<b>Flame Retardant</b>	Non Fire Rated	
<b>Low Temperature</b> (No Crack at:)	DIN 53357	-20°C
<b>RF Weldable</b> (Heat Sealable)	Not Recommended	

### Applications

	Frontlit	Billboard	Blockout	Building Wrap	Spirit-Flex Frame	Crystal Tension Frame	Flex Face	Truckside
Application	■	■						

### Ink Printability

Eco Solvent	UV	Latex	Dye Sublimation
■	■	■	

### Available Sizes

Measurements (Metric m)	
Width	Length
1.15	50
1.37	50
1.60	50
2.50	50
3.20	50

Disclaimer: A legally binding guarantee of specific material properties cannot be inferred from this datasheet the values presented are intended only as a guide of performance only. The information is given without guarantee and does not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for their specific purpose.