

Ultima™ Pro Blockout 610

Product Description

Ultima Pro Blockout 610gsm is a double-sided banner incorporating 500 x 500 denier, 28 x 28 woven base cloth construction. Having a high-quality hybrid / semi-coated smooth and even surface on both sides combined with a woven base cloth means excellent print and lay flat consistency unlike other lighter weight products. It is ideal for indoor and outdoor applications under moderate weather conditions. It is suitable for Eco-Solvent, UV and Latex printing and is B1 fire rated. Available up to 5 metres.

Material Details

CHARACTERISTICS	TEST METHOD	METRIC
Support Cloth (Weave)	DIN 60001	Polyester (28 x 28)
Yarn (Thickness)	DIN EN ISO 2060	500 x 500
Type of Coating	N/A	PVC
Total Weight	DIN 53352	610gsm
Tensile Strength	DIN 53352	Warp 1850 - Weft 1350 N/5 cm
Tear Strength (Warp/weft)	DIN 53356	Warp 235 - Weft 220 N
Flame Resistance	DIN 75200	B1
Low Temperature (No Crack at:)	DIN 53357	-20°C
RF Weldable (Heat Sealable)		✓

Applications

	Frontlit	Billboard	Blockout	Building Wrap	Spirit-Flex Frame	Crystal Tension Frame	Flex Face	Truckside
Application	■		■					

Ink Printability

Eco Solvent	UV	Latex	Dye Sublimation
■	■	■	

Available Sizes

Measurements (Metric m)	
Width	Length
1.37	50
1.60	50
2.50	50
3.20	50
5.00	50

Disclaimer: A legally binding guarantee of specific material properties cannot be inferred from this datasheet the values presented are intended only as a guide of performance only. The information is given without guarantee and does not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for their specific purpose.