

Product Description

Fabritac is a 350gsm easy apply, removable self-adhesive fabric wall covering that can be fitted to many surfaces and repositioned while retaining its adhesion without leaving a residue. FabriTac has a textured surface, with an excellent white point, is quick drying, water resistant and 'Kiss Cuts' cleanly. Its high opacity prevents the translucency problems associated with comparable products. Ideal for temporary wall covering applications for event, retail and exhibition environments. It is suitable for Eco-Solvent, UV and Latex printing. Available in 1.37 and 1.52 metre rolls.

Material Details

CHARACTERISTICS	TEST METHOD	METRIC
Support Cloth	DIN 60001	Polyester
Yard dtex	DIN EN ISO 2060	166 x 166 dtex
Adhesive	White Repositionable Adhesive	
Opacity	ISO 2471	99%
White Point	ISO 105-J02: 1997	90 out of 100
Total Weight	ISO 534	350gsm
Release Paper	Paper Liner 100g (Both sides PE)	
Storage Recommendation	<ul style="list-style-type: none"> All Ultraflex materials should be stored in their original packaging. FabriTac should be stored in temperatures between 10° and 20°C and a relative humidity of 20% - 60%. 	
Flame Retardant	Non Fire Rated	

Application Information

Please see installation guidelines.

Applications

	Outdoor Applications	Windows	Floor Decals	Wall Covering	Badges	Column Wraps
Application		■	■	■	■	■

Ink Printability

Eco Solvent	UV	Latex	Dye Sublimation
■	■	■	

Available Sizes

Measurements (Metric m)	
Width	Length
1.37	50
1.52	50

Disclaimer: A legally binding guarantee of specific material properties cannot be inferred from this datasheet the values presented are intended only as a guide of performance only. The information is given without guarantee and does not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for their specific purpose.

