

## Poplin PES U240

### Product Description

Poplin PES is our most popular uncoated frontlit textile. It has a knitted 240gsm construction for easy stretch on SEG frame systems and exhibition structures and is crease and wrinkle resistant. It is suitable for Latex and Dye Sublimation printing. It is B1 fire rated. Available up to 5.05 metres wide.

### Material Details

CHARACTERISTICS	TEST METHOD	METRIC
Support Cloth	DIN ISO 2076	Polyester
Type of Coating	N/A	Dye Sub & Latex Compatible
Total Weight	DIN EN ISO 2286-2	240gsm
Binding	Knitwear	
Salvage	Loose Selvedge	
Flame Resistance	DIN 4102	B1 & M1

### Applications

	Exhibition Walls & Roof Linings	Frontlit Outdoor Short Term	Window Blinds	Pasted Wallcovering (One piece)	SEG Frames	Backlit SEG Frames	Barrier Jackets	Fence Dressing	Flags
Application		■			■				

### Ink Printability

Eco Solvent	UV	Latex	Dye Sublimation
		■	■

### Available Sizes

Measurements (Metric m)	
Width	Length
1.55	50
2.50	50
3.10	50
5.05	50

Disclaimer: A legally binding guarantee of specific material properties cannot be inferred from this datasheet the values presented are intended only as a guide of performance only. The information is given without guarantee and does not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for their specific purpose.