

## Poplin Opaque U230

### Product Description

Poplin Opaque 230gsm is a knitted lightweight blackout textile with a soft finish that is crease resistant and allows for a slight stretch when installing into SEG frame systems. It is 100% PVC free and recyclable, can be easily wrapped and stapled around timber framework to create exhibition stand walls or used for indoor banner applications with no show through. It is suitable for UV, Latex and Dye Sublimation printing. It is EN13501-1/B-s1, d0 fire rated. Available up to 5.05 metres wide.



### Material Details

CHARACTERISTICS	TEST METHOD	METRIC
Support Cloth	DIN ISO 2076	100% Polyester
Type of Coating	N/A	Polyurethane
Tensile Strength	DIN EN ISO 13934-1	448/683 N/5cm
Total Weight	DIN EN ISO 2286-2	230gsm
Surface Finish	N/A	Semi-Dull (Matt)
Flame Resistance	EN13501-1	B-s1, d0

### Application Information

Poplin Opaque is 100% PVC free/recyclable and crease resistant, when used as large wall graphics we recommend that it's rolled onto a core before shipping. Recommended Dye Sublimation temperature of 180°C. Poplin Opaque has the highest flame retardant classification of any internal textile. EN 13501-1 provides a classification for flammability, smoke production and dripping.

### Applications

	Exhibition Walls	Blockout	Window Blinds	Pasted Wallcovering (One piece)	SEG Frames	AV Screen Surrounds	FabTrack/ Descor	Fence Dressing	Flags
Application	■	■	■		■	■	■		

### Ink Printability

Eco Solvent	UV	Latex	Dye Sublimation
	■	■	■

### Available Sizes

Measurements (Metric m)	
Width	Length
3.20	50
5.05	50

Disclaimer: A legally binding guarantee of specific material properties cannot be inferred from this datasheet the values presented are intended only as a guide of performance only. The information is given without guarantee and does not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for their specific purpose.